

# *PCS 414 50 psi Medical Air Compressor*

## *Hospital Grade Performance in a Quiet, Durable Package*



The Timeter® PCS 414 portable air compressor delivers hospital grade performance in a quiet and durable package. Ideal for continuous use in the professional environment, or as a sturdy homecare rental unit. The PCS 414 features a sound-dampened steel case which is designed to be quiet and lightweight while minimizing potential for damage.

The PCS 414 has been engineered for long service life, and is rated for continuous or intermittent use at an output rating of 14 lpm @ 50 psig. Permanently lubricated heavy-duty bearings are designed to operate **24 hours a day, 365 days a year**. The PCS 414 features a hospital grade plug and meets UL 60601-1 for institutional use. A vibration-free 0-100 psi gauge delivers accurate readings while a dial-and-lock pressure regulator ensures that the desired pressure and air flow setting remains constant. Cool-running and lightweight, the PCS 414 is ideal for use with high-pressure and low-pressure aerosol administration devices, including large and small volume nebulizers.

Day in and day out, the PCS 414 delivers hospital grade performance in a durable package.



# PCS 414 50 psi Medical Air Compressor



The optional Transfer Cart facilitates moving the PCS 414 or raising it to bed level, and the integrated cabinet provides a convenient storage area for accessories.



The TZ120 8" J Bracket, TZ111 Short J Bracket, and TZ85 Right Angle Adapter allow for easy attachment of various devices to the PCS 414.

## SPECIFICATIONS

### Domestic - 115 volt, 60 Hz

Dimensions: 8-1/2" W x 21" D x 13-1/2" H  
Weight: 26.5 lbs.  
Output: 14 lpm @ 50 psig/28 lpm @ 20 psig  
Dew Point Depression: ambient air  
Outlet: DISS male (keyed for oxygen)  
Sound level: 53 dBA  
Pressure Gauge: 0-100 psi  
Pressure Regulator: 0-50 psi  
Power: 4.6 amps (nominal)  
Power Cord: #18-3 x 6' 7"  
Plug: molded hospital grade  
Electrical Protection: 8.0 amp fuses (2)  
Ground Impedance: 0.1 ohms maximum  
Warranty: one year  
Approvals: ETL  
Meets HCPCS Code: E0565

### International - 230 volt, 50-60 Hz

Dimensions: 21 cm W x 53.3 cm D x 34.3 cm H  
Weight: 11.6 kg  
Output: 14 lpm @ 50 psig/19 lpm @ 20 psig  
Dew Point Depression: ambient air  
Outlet: DISS male (keyed for oxygen)  
Sound Level: 50 dBA  
Pressure Gauge: 0-100 psi  
Pressure Regulator: 0-50 psi  
Power: 1.7 amps (nominal)  
Power Cord: #16-3 x 3 m  
Plug: none  
Electrical Protection: 3.15 amp fuses (2)  
Ground Impedance: 0.1 ohms maximum  
Warranty: one year  
Approvals: ETL

## ORDERING INFORMATION

**T14614** PCS 414 Air Compressor, 115 volt, 60 Hz  
**T14615** PCS 414 Air Compressor, with J bracket, 115 volt, 60 Hz  
**T14618** PCS 414 Air Compressor, 230 volt, 50-60 Hz

## ACCESSORIES

**T16159** Portable Transfer Cart  
**TZ85** Right Angle Adapter, oxygen female DISS inlet & oxygen male DISS outlet  
**TZ111** Short J Bracket, oxygen female DISS inlet & oxygen male DISS outlet  
**TZ120** 8" J Bracket, oxygen female DISS inlet & oxygen male DISS outlet  
**TZ70** Cooling Coil and Condensation Trap, oxygen female DISS fitting



T14618  
only



**EMERGO EUROPE**  
Prinsessegracht 20  
2514 AP The Hague  
The Netherlands



Allied Healthcare Products, Inc. • 1720 Sublette Avenue • St. Louis, MO 63110 USA  
314/771-2400 • 800/444-3954 • FAX: 314/771-0650 • www.alliedhpi.com

U.S.  
Toll Free: 800/444-3940  
FAX: 800/477-7701

Canada & Mexico  
Toll Free: 800/446-0552  
FAX: 800/246-6201

International  
Telephone: 314/268-1683  
FAX: 314/771-5183

ISO 13485: 2003

©Allied Healthcare Products, Inc.®

All specifications are nominal and subject to change without notice.

Form 10-00-0080  
Rev. April 2018