

The Evolution of Resuscitation Continues!

Introducing the AutoVent™ 4000 Series Transport Ventilator with optional CPAP.

- Pneumatically powered ... durable and light, with all basic models weighing less than 5 lbs.
- Independent settings for the critical ventilation parameters of Breaths Per Minute, Inspiratory Time, Tidal Volume, and Airway Pressure Relief.
- Manual Breath Button and Anti-Breath Stacking standard on all models.
 - Large color-coded Manometer Gauge along with a full set of alarms to ensure optimal performance and patient safety.
 - Optional Air Mixing provides 65% O₂ concentration for extended cylinder life during lengthy transports.
 - **The capabilities of ventilation and CPAP in one system!**



L760	L761	L762	L763
<ul style="list-style-type: none"> □ Pneumatic Operation □ Adjustable Tidal Volume □ Adjustable BPM □ Child and Adult Settings □ Internal Demand Valve □ Anti-Breath Stacking □ Manometer Readout □ Adjustable Pressure Relief with Alarm □ Low Source Gas Pressure Alarm □ Color-coded Labels and Gauge for Initial Settings □ Manual Breath Button 	<ul style="list-style-type: none"> □ Pneumatic Operation □ Adjustable Tidal Volume □ Adjustable BPM □ Child and Adult Settings □ Internal Demand Valve □ Anti-Breath Stacking □ Manometer Readout □ Adjustable Pressure Relief with Alarm □ Low Source Gas Pressure Alarm □ Color-coded Labels and Gauge for Initial Settings □ Manual Breath Button □ Air Mix Mode 	<ul style="list-style-type: none"> □ Pneumatic Operation □ Adjustable Tidal Volume □ Adjustable BPM □ Child and Adult Settings □ Internal Demand Valve □ Anti-Breath Stacking □ Manometer Readout □ Adjustable Pressure Relief with Alarm □ Low Source Gas Pressure Alarm □ Color-coded Labels and Gauge for Initial Settings □ Manual Breath Button □ Air Mix Mode □ Electronic Alarm Package 	<ul style="list-style-type: none"> □ Pneumatic Operation □ Adjustable Tidal Volume □ Adjustable BPM □ Child and Adult Settings □ Internal Demand Valve □ Anti-Breath Stacking □ Manometer Readout □ Adjustable Pressure Relief with Alarm □ Low Source Gas Pressure Alarm □ Color-coded Labels and Gauge for Initial Settings □ Manual Breath Button □ Electronic Alarm Package



All models available with optional CPAP

SPECIFICATIONS

Dimensions: 2.9" x 9.6" x 6.5" with CPAP: Weight: 3.7 lbs. with CPAP: (5.2 lbs. w/CPAP)	Dimensions: 2.9" x 9.6" x 6.5" with CPAP: Weight: 4.2 lbs. with CPAP: (5.7 lbs. w/CPAP)	Dimensions: 2.9" x 9.6" x 8.0" with CPAP: Weight: 4.9 lbs. with CPAP: (6.4 lbs. w/CPAP)	Dimensions: 2.9" x 9.6" x 8.0" with CPAP: Weight: 4.4 lbs. with CPAP: (5.9 lbs. w/CPAP)
--	--	--	--

<p>Gas Supply Pressure: 40.6 to 87.0 psi oxygen DISS</p> <p>Breaths Per Minute: Accuracy: ±10% Range: 1 second inspiratory time = 0 to 30 bpm Range: 2 second inspiratory time = 0 to 20 bpm</p> <p>Tidal Volume: Accuracy: ±10% with 100% oxygen Range: 1 second inspiratory time = 200 ml to 600 ml Range: 2 second inspiratory time = 400 ml to 1200 ml</p> <p>Inspiratory Time: Accuracy: ±10%</p> <p>Safety Pressure Relief: Adjustable from 20 to 80 cmH₂O ±10%</p> <p>Low Source Gas Alarm: Activates at 275 to 262 kPa (40 to 38 psi) source pressure</p> <p>Oxygen Inlet Filter: 65 micron sintered bronze</p> <p>Burst Pressure: 250 psig minimum (1724 kPa)</p> <p>Leakage: Designed so that oxygen is not allowed to leak through any seals or fittings</p> <p>Gauge: 0-100 cm H₂O (accuracy ±2% of reading)</p> <p>Inspiratory and Expiratory Resistance: 5 cm H₂O maximum</p> <p>Inadvertent PEEP: ≤ 2 cm H₂O</p>	<p>Inadvertent Continuing Expiratory Pressure: ≤ 2 cm H₂O</p> <p>Dead Space: ≤ 5.5% of minimum tidal volume</p> <p>Peak Inspiratory Flow: 100 lpm for 2 seconds</p> <p>Pressure for Initiation of Breath: -2 cm H₂O maximum</p> <p>Operating Conditions: 0° to 122°F</p> <p>Storage / Shipping Conditions: -40° to 140°F</p> <p>Oxygen Concentration: 100% or 65% with mixing</p> <p>Electronic Alarm Package (optional): High Airway Pressure Alarm: Range: 15 to 80 cm H₂O Accuracy: 5% Low Airway Pressure Alarm: Range: 0 to 30 cm H₂O Accuracy: 5% Low Source Gas</p> <p>Electronic Alarm Battery Life: Greater than 40 hours at room temperature (with Low Battery Alarm)</p> <p>Alarm Sound Level: Greater than 60 decibels</p> <p>CPAP Pressure*: Adjustable from 5-20cm H₂O</p>
---	---

ORDERING INFORMATION

L760 AutoVent 4000	L761 AutoVent 4000 with Air Mix Mode	L762 AutoVent 4000 with Air Mix Mode & Electronic Alarm Package	L763 AutoVent 4000 with Electronic Alarm Package
--------------------	--------------------------------------	---	--

Add CPAP to each model number to include CPAP option

ACCESSORIES			
L599-130	Ventilator Circuit, 10/case	800149	Internal Air Filter, 3/pkg.
L535026	Oxygen Hose, 6' with DISS fittings	800148	CPAP Ventilator Circuit, 6/pkg.
L270-220	Oxygen Regulator		



All specifications are nominal and subject to change without notice.
All systems comply with International Standards of FDA, CE and Canada.



Allied Healthcare Products, Inc. • 1720 Sublette Avenue • St. Louis, Missouri 63110
314/771-2400 • 800/444-3954 • Fax: 314/771-0650 • www.alliedhpi.com
International offices in Europe, Asia, and South America

U.S.
Toll Free: 800/444-3940
Fax: 800/477-7701

Canada & Mexico
Toll Free: 800/446-0552
Fax: 800/246-6201

International
Telephone: 314/268-1683
Fax: 314/771-5183