

Demand/Resuscitator Valve



L063-03R

The LSP Demand/Resuscitator Valve is designed to provide 100% oxygen to a breathing or non-breathing patient in an emergency situation. The valve is designed for use with a mask, endotracheal tube, or tracheotomy tube.

The Demand Resuscitation Valve complies with AHA guidelines recommending that 100% oxygen be given to victims of a heart attack and/or smoke inhalation. The valve can be used in conjunction with a portable oxygen cylinder equipped with a pressure regulator or with a central oxygen source. The valve operates on a regulated oxygen supply of 40-60 psig (275 to 413 kPa) and reduces this pressure to a physiologically acceptable level with a pressure limit of 60 ± 5 cm H₂O. This prevents excessive buildup of intrapulmonary pressures and over-inflation of the lungs.

The slight negative pressure created by a spontaneously breathing patient's inspiratory effort triggers the valve from a non-flow state to a flowing state. The greater the inspiratory effort, the higher the flow. When the inspiratory effort stops, the flow stops. The non-breathing valve permits it to be used as a resuscitator in combination with a manually operated button located on top of the valve.

The Demand/Resuscitator Valve provides an accurate constant flow rate of 40 lpm to help prevent gastric inflation, as recommended by the AHA. It is also available with a minimum flow rate setting of 160 lpm.

Key Features

- Maximum cylinder use ... flow rate of 40 lpm is maintained at cylinder pressures between 500-2200 psig (3447 to 15168 kPa), allowing for complete use of cylinder contents
- Easy to clean and service ... valve obstruction may be removed during resuscitation with minimal interruption; valve may also be chemically disinfected
- Compact, lightweight and durable ... will withstand corrosive materials and harsh weather conditions

Demand/Resuscitator Valve

SPECIFICATIONS

40 lpm Flow Rate (restricted flow): As required in demand mode, 0-40 lpm at 50 psig (344 kPa);
in resuscitation mode, a constant flow of 40 lpm at 50 psig (344 kPa)

160 lpm Flow Rate: As required in demand mode, 0-160 lpm at 40 psig (275 kPa);
in resuscitation mode, a constant flow of 160 lpm at 40 psig (275 kPa)

Delivery Pressure: 60±5 cm H₂O unless otherwise indicated on the demand valve

Crack Pressure: 0 to -2 cm H₂O (0 to -8 in. H₂O)

Exhalation Resistance:

LPM	cm H ₂ O (maximum)
0-10	1.5
11-70	3.8
71-160	6.4

Dead Space: 8 ml (excluding mask)

Supply Pressure: 40 to 60 psig (275 to 413 kPa)

Operating Temperature: -30° F to 125° F (-34.4 C to 51.7 C)

Storage Temperature: -40° F to 160° F (-40 C to 71.1 C)

Inlet Fitting: standard 1male oxygen DISS

Filter: 25 micron wire mesh

Outlet: 22 mm outside diameter x 15 mm inside diameter

Materials: body - anodized aluminum; cover - polycarbonate; outlet - polysulfone;
inlet fitting - plated brass

ORDERING INFORMATION

L063R	Demand/Resuscitator Valve, with 6' (1.8 m) oxygen hose, 40 lpm flow rate
L063-03R	Demand/Resuscitator Valve, with 6' (1.8 m) oxygen hose, adult cuffed mask, 40 lpm flow rate
L063-05R	Demand/Resuscitator Valve, 40 lpm flow rate
L063	Demand/Resuscitator Valve, with 6' (1.8 m) oxygen hose, 160 lpm flow rate
L063-030	Demand/Resuscitator Valve, with 6' (1.8 m) oxygen hose, adult cuffed mask, 160 lpm flow rate
L063-050	Demand/Resuscitator Valve, 160 lpm flow rate
L099-004	Adult Cuffed Mask, reusable, size 4
L099-005	Adult Cuffed Mask, reusable, large, size 5
L535026	Oxygen Hose, 6' (1.9 m), with DISS fittings

For information on international configurations,
contact an Allied Healthcare international sales or customer service representative.



L063-03R Demand/Resuscitator Valve
with L535026 oxygen hose and L099-004
adult cuffed mask



EMERGO EUROPE
Prinsessegracht 20
2514 AP The Hague
The Netherlands



Allied Healthcare Products, Inc. ▪ 1720 Sublette Avenue ▪ St. Louis, MO 63110 USA
314/771-2400 ▪ 800/444-3954 ▪ FAX: 314/771-0650 ▪ www.alliedhpi.com

U.S.
Toll Free: 800/444-3940
FAX: 800/477-7701

Canada & Mexico
Toll Free: 800/446-0552
FAX: 800/246-6201

International
Telephone: 314/268-1683
FAX: 314/771-5183

ISO 13485: 2003

©Allied Healthcare Products, Inc.®

All specifications are nominal and
subject to change without notice.

Form 90-00-0011
Rev. May 2017